

HPE ProLiant DL160 Gen9 Server

Right-size performance, storage for
space-constrained environments



The right balance

The HPE ProLiant DL160 Gen9 Server delivers the right balance of performance, storage, reliability, manageability, and efficiency in a compact chassis. This space-conscious server meets the needs of a diverse set of customers—from SMBs to service providers. The DL160 Gen9 Server is designed to handle a wide range of deployments—from general-purpose IT infrastructure to emerging workloads such as cloud and Big Data in distributed computing environments.

Addresses the business needs of SMBs

Even though budgetary pressures force small-to medium-sized businesses (SMBs) to do more with fewer resources, many companies continue to look for new ways to grow their businesses and remain competitive in today's evolving business environment. To meet those goals, SMBs need an IT infrastructure that is quick to set up and easy to maintain. They also need scalable solutions that can grow right along with their businesses. Ideally, they want "everything IT" converged into a single platform.

SMBs can get what they need with the HPE ProLiant DL160 Gen9 Server—a fully integrated platform designed to perform and scale. Offering standard HPE Integrated Lights-Out (iLO) capabilities for simplified IT infrastructure management, 16 slots for DDR4 memory, eight drives, and two standard NIC ports, HPE ProLiant DL160 Gen9 Server offers the ideal set of features for meeting SMBs' everyday business needs. And with the DL160 Gen9 Servers' built-in virtualization features, server, and storage utilization increases, and IT infrastructure runs more efficiently at a lower cost. HPE ProLiant DL160 Gen9 Server enables SMBs to start small, and scale easily and cost-effectively, as their businesses grow.

Meets the requirements of service providers

Faced with an ever-growing customer base, service providers need an agile IT infrastructure that scales readily and consumes minimal space and energy. And to support today's mega data-centric trends—Big Data and cloud computing—service providers need to optimize their IT environments and move to a distributed computing model where servers are deployed as compute nodes, network nodes, and database nodes.

With 16 DIMM slots, 92 percent efficient power supply, ASHRAE A3/A4¹ compliance (for higher ambient temperature support), dense 2P/1U design, and optional FlexibleLOM capability, the ProLiant DL160 Gen9 Server enables service providers to minimize the operational costs of energy and space—making it a perfect match for today's hyperscale environments.

Hewlett Packard Enterprise Services

Let Hewlett Packard Enterprise help guide you and your business through the rapidly changing IT landscape. HPE Technology Services delivers confidence, reduces risk, and helps you realize greater agility and stability.

¹ See hp.com/servers/ASHRAE for details.

Technical specifications

HPE ProLiant DL160 Gen9 Server

Compute	Up to 2 Intel® Xeon® E5-2600 v3/v4 Series, 4/6/8/10/12/14/16/18 cores PCIe 3.0, up to 3 available slot(s)
Memory	HPE SmartMemory (16) DDR4, up to 2400 by 1 TB max at launch), support for NVDIMM (third-party)
Storage	Standard HPE Dynamic Smart Array B140i, optional HPE Smart Array Controllers, and HPE Smart HBA via PCIe stand-up cards
HPE SmartDrive	8 SFF/4 LFF max, HDD/SSD, M.2 enabled
Networking	Embedded 2x 1GbE, optional FlexibleLOM slot on riser
VGA/USB/SD ports	Rear video, 3x USB 3.0 and 1x USB 2.0 (std), 1x USB 3.0 (opt of SFF models), microSD, Dual microSD optional
System ROM	UEFI and Legacy BIOS
Converged management	HPE OneView with HPE iLO Advanced
Support management	HPE Insight Online with enhanced mobile application
Embedded management	HPE iLO 4, Intelligent Provisioning, SUM, RESTful Interface Tool, Scripting Tools for Microsoft® Windows Server® PowerShell
Power and cooling	Up to 92 percent efficient (80 PLUS gold certified) 550 W multi-output ¹ , 900 W RPS Hot swap fans with optional redundancy
Industry compliance	ASHRAE A3 and A4,1 ENERGY STAR®
Form factor/Chassis depth	Rack (1U), 23.9" (SFF), 23.9" (LFF)
Serviceability—easy install rails	Standard
Warranty	3/1/1

- Our **consulting** services provide advice and guidance to safely move your workloads to newer technologies.
- HPE implementation and installation services enable faster, more reliable startup of your new ProLiant Gen9 servers, and our support portfolio allows you to get connected and get back to business fast.
- We recommend HPE **Proactive Care** for ProLiant Gen9 servers to prevent issues and resolve problems quickly and efficiently.
- HPE **Foundation Care** provides a choice of coverage levels and response times for hardware and software support.
- HPE **Datacenter Care** enables you to operate and evolve your IT environment at a lower cost and with more agility, including our **Flexible Capacity** Service to acquire IT without impacting capital budget.
- Our support technology lets you tap into the knowledge of millions of devices and thousands of experts to stay informed and in control, anywhere, any time.



hpe.com/qref/dl160gen9



Sign up for updates

★ Rate this document

**Hewlett Packard
Enterprise**

Learn more at
hpe.com/servers/dl160gen9

© Copyright 2014-2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprises shall not be liable for technical or editorial errors or omissions contained herein.

Intel Xeon is a trademark of Intel Corporation in the U.S. and other countries. ENERGY STAR is a registered mark owned by the U.S. government. Intel Xeon is a trademark of Intel Corporation in the U.S. and other countries. Microsoft and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. SD and microSD are trademarks or registered trademarks of SD-3C in the United States, other countries or both.

4AA5-4083ENW, March 2016, Rev. 4