Product profile



Ci7O -Ex Intrinsically Safe Mobile Computer

Based on the successful 70 Series mobile computer family, the Ci70 combines global certifications for hazardous environments with today's cutting-edge technologies.

- Global approvals for explosive environments-ATEX through IECEx to NEC
- Available high performance 2D near/ far scanning technology—a first for intrinsically safe mobile computers
- Comprehensive wireless network coverage–WWAN or WLAN and Bluetooth 2.1 for rapid data exchange
- Available RFID reading capability supporting a wide range of frequencies–LF, HF, or UHF
- As with devices based on the 70 Series platform, the Ci70 offers a high level of compatibility with Intermec Developer Library software applications and tools

Traditionally, mobile computers for use in hazardous environments have been hamstrung with outdated technology and limited configuration options, requiring users to make significant tradeoffs. But Intermec and ecom[®] have combined their expertise to create a new paradigm in intrinsically safe mobile computing that doesn't require compromises: the Ci70.

Featuring the highest number of global approvals for hazardous environments, the Ci70 is the best choice for workers in the chemical, oil and gas, and pharmaceutical industries. It meets or exceeds stringent requirements for gases, vapors and liquids, dusts, and fibers.

The Ci70 includes many breakthrough advances now available in an intrinsically safe mobile computer for the first time. Complete wireless networking capabilities– from WWAN to WLAN and Bluetooth 2.1–help ensure rapid data exchange, even where reception conditions prove challenging. Available near/far imaging technology now allows operators in hazardous environments to scan bar codes from near contact to over 50 feet away. Even radio frequency detection (RFID) capability can be added via a head module. Because Ci70 is built on the 70 Series architecture, it is fully compatible with relevant development tools and applications in the Intermec Developer Library, and even includes many of the same design elements. Those accustomed to Intermec mobile computers will find the Ci70's laseretched keypad to be instantly familiar. The Ci70 is also compatible with FlexDock, Intermec's modular charging system, by means of a field-replaceable cup.

When the reliability, efficiency and accuracy of your operations are the foundation to your competitive advantage, there is no room for compromise. With the Ci70 and full family of 70 Series mobile computers, you have the unsurpassed performance and reliability to run your operations with confidence.

The i.roc[®] Ci70 -Ex is manufactured and serviced exclusively by ecom instruments. This product will be available for purchase only from ecom authorized distributors and their partners.





Physical

Dimensions (Standard Configuration): 225 x 85 x 58 mm (9.8 x 3.3 x 2.3 in.) Dimensions (Includes Optional Head Module): 249 x 85 x 58 mm (8.8 x 3.3 x 2.3 in.) Weight (Includes Battery): 900 g (2 lbs)

Environmental

Operating Temperature: -20°C to +50°C (-4°F to +120°F) Storage Temperature: -20°C to +60°C (-4°F to +140°F) Drop Specification: 1.2 m (4 ft) according to MIL-STD-810G at -20°C and +50°C (-4°F and +120°F) Electrostatic Discharge: 8 kV contact discharge, ± 15 kV air discharge Rain & Dust Resistance: IP65

Battery

Type: Replaceable and rechargeable lithium ion pack, IEEE 1725 compliant **Capacity:** 4000 mAh (3.7 V)

Hardware

Microprocessor: Texas Instruments 1GHz multi-engine processor architecture

Memory and Storage: 512 MB RAM; 1 GB flash ROM; customer-accessible microSD slot for removable memory cards up to 32 GB

Display: Transmissive TFT-LCD touchscreen display; 8.9 cm (3.5 in); VGA (480 x 640 pixels); 65,536 colors (16-bit RGB); high-durability with Gorilla Glass[®]; LED backlight; ambient light sensor

Keypad: Backlit numeric or QWERTY layout; both keypad options feature hard keycaps with laser-etched legends

GPS: A-GPS with 12 channels; network independent autonomous mode; supports assisted operation via WAN Sensors: Accelerometer, ambient light

Operating System

Microsoft[®] Windows Embedded Handheld built on Windows 6.5.3 technology

Optional Software

App Development: Intermec Developer Library Data Management: Skynax® Mobility Management System

Device Management: Intermec SymartSystems[™] support includes ScanNGo provisioning for use alone or with device management software from Intermec ISVs Device Health Monitoring: Remote access requires SmartSystems Management option

Interfaces

USB Full Speed 2.0 Client, IrDA

Integrated Radios

- Optional Wireless WAN: UMTS/HSDPA/HSUPA UMTS Frequencies: 800, 850, 900, 1900, 2100 MHz CSM/GPRS Frequencies: 850, 900, 1800, 1900 MHz Max Data Rate (Network Dependent): 5.76 Mbps uplink, 14.4 Mbps downlink Antenna: Internal
- Optional Wireless WAN: CDMA/EVDO Rev. A CDMA Frequencies: 800, 1900 MHz Max Speeds (Network Dependent): 1.8 Mbps uplink, 3.1 Mbps downlink Antenna: Internal
- Wireless LAN: IEEE® 802.11 a/b/g/n, dual-band, Cisco

CCXv4 compliant

- Security: Wi-Fi Certified for WPA and WPA2, WAPI Certified
- Authentication: 802.1x
- Encryption: AES, TKIP, WEP (64 or 128 bit) Wireless PAN: Integrated Bluetooth[®] Class II,

Version 2.1+EDR

Operating Channels: 0 to 78 (2402 to 2480 MHz) Data Rate: 1, 2, 3 Mbps Antenna: Internal

Imaging & Reading

With optional factory replaceable head modules, the imaging and reading capabilities of Ci70 can be enhanced:

- Near/far range 2D area imager-offering the unparalleled flexibility to read 1D and 2D bar codes, omni-directionally, at distances from 15 cm to over 15 m
- Linear laser-scan 1D bar codes at close proximity
 RFID reader-supporting HF, LF, and UHR
- RFID Teader=Supporting FF, EF, and OFR

Audio

Loudspeaker; wireless Bluetooth headset support; VOIP, speech recognition and audio recording capabilities via headset

Optional Accessories

Compatible with FlexDock modular docking and charging system. Additional accessories include: carrier strap; microSD card; display protection film; handle; and leather case.

Regulatory Approvals & Conformity

Safety: 60950-1 EMC: FCC, CE Laser: IEC/EN 60825-1 Class 2 Environmental: WEEE, RoHS Radio: FCC, CE Battery: IATA

Hazardous Environment Certifications







by Honeywell

North America Corporate Headquarters 6001 36th Avenue West Everett, Washington 98203 Phone: (425) 348 2600 Fax: (425) 355 9551



Corporate Headquarters ecom instruments GmbH Industriestraße 2 97959 Assamstadt Germany Phone: (+49) 6294 4224 - 0 Fax: (+49) 6294 4224 - 100 Email: sales@ecom-ex.com Website: www.ecom-ex.com

North America Headquarters

ecom instruments Inc. 1779 Westborough, Suite 102 Katy, Texas 77449 Phone: (281) 496 5930 Fax: (281) 496 2321 Email: info.us@ecom-ex.com Website: www.ecom-ex.us



© 2014 Honeywell International Inc. 612217-C 12/14