

# HCH-3006-CHG

## Charger Specifications:

### Temperature Limits:

Operating Range: 0°C to 35°C  
32°F to 95°F

Storage Range: -40°C to 85°C  
-40°F to 185°F

### Dimensions:

Length: 165 mm  
Width: 159 mm  
Height: 66 mm  
Weight: 0.54 g

### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



## Compatible Batteries

### HMC3X00-Li(S) Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.05.16

## Maximize performance with the GTS 6-Bay MC3000 Battery Charger



**Dual-chemistry charger**  
Supports Li-Ion and Li-Polymer chemistries.

Made of highly rugged aerospace grade aluminum housing.

**More efficiency in less space**  
Charges 50% more batteries in same space as OEM chargers.

**Hassle-free mounting**  
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

**Tri-color charging indications**  
A charging LED indicates charging status.



Includes power supplies and cable.

### For Pricing or Additional Information Contact:

Global Technology Systems, Inc.  
550 Cochituate Road Framingham, MA 01701  
US: 1.800.267.2711 ■ EU: 00800.5390.5390  
[www.GTSpower.com](http://www.GTSpower.com) @GTSpower1

